



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP24V15RT2U

BP24V15RT2U - External Battery Pack for UPS System

Highlights

- Extends the runtime of compatible Tripp Lite UPS Systems that accept a 24V DC external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable
- 2-year warranty



Description

BP24V15RT2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems: OMNIVS1500XL, OMNIVSINT1500XL, SU750XL, SU750RTXL2U, SU1000XL, SU1000RTXL2Ua, SUINT1000RTXL2Ua, SMART750RML2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP24V15RT2U External Battery Pack
- Rack/tower brackets
- Owner's manual with warranty information

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty
- NOTE: LIMIT OF 1 BP24V15RT2U PER UPS, SEE BP24V70-3U FOR MULTI-PACK COMPATIBILITY

Specifications

BATTERY	
Connects to UPS via	Attached 24VDC 75amp connector
DC system voltage	24VDC

Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	29.25
Shipping weight (kg)	13.2
Shipping Dimensions (HWD/in)	21.5 x 15 x 29.25
Shipping Dimensions (HWD/cm)	54 x 38 x 74.3
Unit weight (lbs)	27.25
Unit weight (kg)	12.3
Unit Dimensions (HWD/in)	3.5 x 17.25 x 10.5
Unit Dimensions (HWD/cm)	8.89 x 43.8 x 26.7
Material of construction	Polycarbonate
Form factors supported	2U rack/tower
CERTIFICATIONS	
Certifications	CE
WARRANTY	
Product Warranty Period	2 years
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Extended Warranties		
WEXT3-BP24V	3-Year Extended Warranty - For All 24V Battery Packs	Qty: [optional]
WEXT5-BP24V	5-Year Extended Warranty - For All 24V Battery Packs	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3827.